# HYDROBRONPI-60E







SCL

SSS

kW 22


kW 17 | % 76 | 6,5 | m³ 550 | 45 | kg 151 | Ø 200 | 536x274x390 | bar 1,5


54 | 170 | F-503 122 | KIT-1 | KIT-2 | VAL-02, VAL-05

## Features

- Clean Glass System
- Overpressure Safety System
- Heating power: 22kw
- Power transferred to water (kW): 17kw
- Efficiency (%): 76%
- Consumption (kg/h): 6,5kg/h
- Heating capacity (m3): 550m3
- Hopper capacity (l): 45l
- Ceramic inside
- Manufactured in cast-iron and steel
- Weight (kg): 151kg
- Smoke exit tube diameter (mm): 200mm
- Useful oven measures: 536x274x390mm
- Working pressure (bar): 1,5bar
- Maximum logs size (cm): 54cm
- Underfloor heating (m2):170
- Nº radiator elements: 122
- Compatible accesories not included: F-503; KIT-1; KIT-2; VAL-02; VAL-05

5 years guarantee




Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

**www.bronpi.com**

BRONPI
la excelencia en el fuego

©Bronpi Calefacción, S.L. reserves all rights to the images that appear in this document. You may not reproduce or distribute part or all of the photographs and as the text. Both the brand as distinctive symbols are the exclusive property of the company. Violators will be prosecuted according to law.