## **NOA HORNO**







exclusive property of the company. Violators will be prosecuted according to law


























































- CANALIZATION KIT OPTIONAL
- Oasys Plus
- Double Chamber System
- Clean Glass System
- Low Emissions System
- Modulation System
- Model designed for easy access to maintenance service
- Noiseless


S.L. reserves all rights to the images that appear in this document. You may not reproduce or distribute part or all of the photographs and as the text. Both the brand as disting


- Model Compatible with Kit Wifi
- Programmable
- Flame anti-return system
- Chamber overpressure valve
- Power max: 12kw
- Power max-min: 10-4,5kw
- Efficiency (%): 87-89%
- Consumption max-min (kg/h): 2,5-1,1kg/h
- Power consumption (W): 150-300W
- Heating capacity (m3): 250m3
- Tank capacity (Kg): 15kg
- Vermiculite interior Cast-iron burner
- Autonomy (h) (min-max): 6-14h
- Weight (kg): 159kg
- Fume outlet diameter (mm): 80mm











## **Features**

- Air inlet diameter (mm): 50mm
- Forced ventilation: 1x430
- Remote control or switchboard
- S1:Security systems: Safety thermostat pellet, Air flow switch
- Compatible accesories not included:WIFI KIT; CANALIZATION KIT

