







INCLUYE INTERCAMBIADOR-ACUMULADOR TÉRMICO DE FUNDICIÓN.  
 INCLUDES A CAST-IRON HEAT EXCHANGER-ACCUMULATOR.  
 INCLUI INTERCAMBIADOR-ACUMULADOR TÉRMICO EM FUNDIÇÃO.  
 INCLUDE SCAMBIATORE DI CALORE-ACCUMULATORE TERMICO IN GHISA.  
 COMPREND UN ÉCHANGEUR DE CHALEUR-ACCUMULATEUR DE CHALEUR EN FONTE.

		WIFI KIT		CANALIZATION KIT						

## Features

- CANALIZATION KIT OPTIONAL
- Oasys Plus
- Double Chamber System
- Clean Glass System
- Modulation System
- Model designed for easy access to maintenance service
- Model Compatible with Kit Wifi
- Programmable
- Flame anti-return system
- Chamber overpressure valve
- Power max: 12kw
- Power max-min: 10,1-4,9kw
- Efficiency (%): 92-93%
- Consumption max-min (kg/h): 2,4-1kg/h
- Power consumption (W): 150-300W
- Heating capacity (m3): 252m3
- Tank capacity (Kg): 19kg
- Cast-iron interior
- Cast-iron burner
- Autonomy (h) (min-max): 7,9-19h
- Weight (kg): 135kg
- Fume outlet diameter (mm): 80mm
- Air inlet diameter (mm): 50mm
- Forced ventilation: 1x430



Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

[www.bronpi.com](http://www.bronpi.com)



## Features

- Remote control or switchboard
- Hermetic tank
- S1:Security systems: Safety thermostat pellet, Air flow switch
- Compatible accesories not included:WIFI KIT; CANALIZATION KIT